

Battery Charger Series

PowerBase

www.powerbasehk.com

PowerBase Industrial (HK) Ltd.



ROOM 503, TOWER A, NEW MANDARIN PLAZA,
14 SCIENCE MUSEUM ROAD, TST EAST,
KOWLOON, HONG KONG

Tel : (852) 2773 9909, 2773 9939
Fax : (852) 2773 9992
E-mail : info@powerbasehk.com

Designation : Switching Overnight Charger

Charge Channel	Single Channel
Charge Capability	2 AA or AAA NiMH/NiCd Batteries
Charge Current	150 mA / AA 150 mA / AAA
Charge Time	Approx. 14 hrs. NiMH AA 2000mA Approx. 7 hrs. NiMH AAA 1000mA
International Voltage	Switching : 100~240V 50~60Hz (UL, VDE, SAA, BS, JIS)
Features	- 2 AA or AAA size Ni-MH/Ni-Cd batteries can be charged - LED indicator - International Voltage 100~240V

Model No. : C-421S



Cord Cable
UL, VDE, SAA, CH, BS

Dimension (Approximate)	74.6mm(L) x 70mm(W) x 16.2mm(H)
Weight (Approximate)	Charger : 130 g (without battery),
Housing	PC / ABS : Pearl Gray or Pearl White, or Custom Colours

Individual Data sheet

This specifications is only for generally reference, about the Charger and Batteries performance, warranty, modification/designs. Please contact PowerBase for the latest information.

PowerBase®